



### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: MORAVIA - MORAMASTIC 8303 (COMPONENT A) AS16-8303A

### **1.2** Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Paint. For professional user/industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

### **1.3** Details of the supplier of the safety data sheet:

MORAVİA BOYA VE KİMYA SAN.TİC.LTD.ŞTİ FEVZİ ÇAKMAK CADDESİ NO:2 SEFAKÖY/ KÜÇÜKÇEKMECE İSTANBUL - TURKEY Phone.: +90 212 579 13 36 - Fax: +90 212 426 55 12 moravia@moravia.com.tr www.moravia.com.tr

### 1.4 Emergency telephone number:

### SECTION 2: HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture:

### CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Acute Tox. 4: Acute toxicity, Category 4, H312+H332 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411 Eye Dam. 1: Serious eye damage, Category 1, H318 Flam. Liq. 3: Flammable liquids, Category 3, H226 Skin Irrit. 2: Skin irritation, Category 2, H315 Skin Sens. 1: Sensitisation, skin, Category 1, H317

### 2.2 Label elements:

### CLP Regulation (EC) No 1272/2008:



#### Hazard statements:

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects Eye Dam. 1: H318 - Causes serious eye damage Flam. Liq. 3: H226 - Flammable liquid and vapour Skin Irrit. 2: H315 - Causes skin irritation Skin Sens. 1: H317 - May cause an allergic skin reaction **Precautionary statements:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P280: Wear protective gloves/protective clothing/eye protection/face protection P302+P352: IF ON SKIN: Wash with plenty of water P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P370+P378: In case of fire: Use ABC powder extinguisher to extinguish P403+P235: Store in a well-ventilated place. Keep cool

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively

#### Supplementary information:

EUH205: Contains epoxy constituents. May produce an allergic reaction

### Substances that contribute to the classification

reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 ); Xylene; Phenol, methylstyrenated; 2-methylpropan-1-ol

2.3 Other hazards:



### MORAVIA - MORAMASTIC 8303 (COMPONENT A) AS16-8303A

### SECTION 2: HAZARDS IDENTIFICATION (continued)

Product fails to meet PBT/vPvB criteria

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

#### Chemical description: Miscellaneous products

### Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration
CAS:	25068-38-6	reaction product: bis	phenol-A-(epichlorhydrin) ( MW < 700 ) <sup>(1)</sup> ATP CLP00	
EC: Index: REACH:	500-033-5 603-074-00-8 01-2119456619-26- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - 🕀 🏠	25 - <50 %
CAS:	1330-20-7	Xylene <sup>(1)</sup>	ATP CLP00	
EC: Index: REACH:	215-535-7 601-022-00-9 01-2119488216-32- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	10 - <25 %
CAS:	68512-30-1	Phenol, methylstyrer	nated <sup>(1)</sup> Self-classified	
EC: Index: REACH:	270-966-8 Non-applicable 01-2119555274-38- XXXX	Regulation 1272/2008	Aquatic Chronic 3: H412; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	2,5 - <10 %
CAS:	78-83-1	2-methylpropan-1-o	ATP CLP00	
EC: Index: REACH:	201-148-0 603-108-00-1 01-2119484609-23- XXXX	Regulation 1272/2008	Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335; STOT 👔 🔅 🏈	2,5 - <10 %
CAS:	64742-88-7	Solvent naphtha (pe	troleum), medium aliph.(1) Self-classified	
	265-191-7 649-405-00-X 01-2119537181-47- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; Skin Irrit. 2: () () () () () () () () () () () () ()	2,5 - <10 %

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product. **By inhalation:** 

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

### By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

#### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.



### SECTION 4: FIRST AID MEASURES (continued)

### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers ( $CO_2$ ). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

#### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

### 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

### 6.4 Reference to other sections:

See sections 8 and 13.


### SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions





### SECTION 7: HANDLING AND STORAGE (continued)

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

- C.- Technical recommendations to prevent ergonomic and toxicological risks
  - Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.
- D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:5 °CMaximum Temp.:30 °CMaximum time:6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification	Occupational exposure limits		
Xylene	IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>

DALEL	() (	-
DNEL (	(Workers)	

	Short exposure		Long exposure		
Identification		Systemic	Local	Systemic	Local
reaction product: bisphenol-A-(epichlorhydrin) ( $MW < 700$ )	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 25068-38-6	Dermal	8,33 mg/kg	Non-applicable	8,33 mg/kg	Non-applicable
EC: 500-033-5	Inhalation	12,25 mg/m <sup>3</sup>	Non-applicable	12,25 mg/m <sup>3</sup>	Non-applicable
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	289 mg/m <sup>3</sup>	289 mg/m <sup>3</sup>	77 mg/m³	Non-applicable
Phenol, methylstyrenated	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 68512-30-1	Dermal	Non-applicable	Non-applicable	16,4 mg/kg	Non-applicable
EC: 270-966-8	Inhalation	Non-applicable	Non-applicable	57 mg/m <sup>3</sup>	Non-applicable
2-methylpropan-1-ol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 78-83-1	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 201-148-0	Inhalation	Non-applicable	Non-applicable	Non-applicable	310 mg/m <sup>3</sup>



### MORAVIA - MORAMASTIC 8303 (COMPONENT A) AS16-8303A

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	exposure	Long	g exposure
Identification		Systemic	Local	Systemic	Local
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 )	Oral	0,75 mg/kg	Non-applicable	0,75 mg/kg	Non-applicable
CAS: 25068-38-6	Dermal	3,571 mg/kg	Non-applicable	3,571 mg/kg	Non-applicable
EC: 500-033-5	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Xylene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	Non-applicable	Non-applicable	14,8 mg/m <sup>3</sup>	Non-applicable
Phenol, methylstyrenated	Oral	Non-applicable	Non-applicable	4 mg/kg	Non-applicable
CAS: 68512-30-1	Dermal	Non-applicable	Non-applicable	8 mg/kg	Non-applicable
EC: 270-966-8	Inhalation	Non-applicable	Non-applicable	28 mg/m <sup>3</sup>	Non-applicable
2-methylpropan-1-ol	Oral	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
CAS: 78-83-1	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 201-148-0	Inhalation	Non-applicable	Non-applicable	Non-applicable	55 mg/m <sup>3</sup>
PNEC:					
Identification					
reaction product: bisphenol-A-(epichlorhydrin) ( $MW < 700$	STP	10 mg/L	Fresh water	C	),006 mg/L

reaction product: bisphenol-A-(epichlorhydrin) ( $MW < 700$ )	STP	10 mg/L	Fresh water	0,006 mg/L
CAS: 25068-38-6	Soil	0,196 mg/kg	Marine water	0,0006 mg/L
EC: 500-033-5	Intermittent	0,018 mg/L	Sediment (Fresh water)	0,996 mg/kg
	Oral	11 g/kg	Sediment (Marine water)	0,0996 mg/kg
Xylene	STP	6,58 mg/L	Fresh water	0,327 mg/L
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water	0,327 mg/L
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
Phenol, methylstyrenated	STP	2,4 mg/L	Fresh water	0,014 mg/L
CAS: 68512-30-1	Soil	10,5 mg/kg	Marine water	0,0014 mg/L
EC: 270-966-8	Intermittent	0,14 mg/L	Sediment (Fresh water)	52,9 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	5,3 mg/kg
2-methylpropan-1-ol	STP	10 mg/L	Fresh water	0,4 mg/L
CAS: 78-83-1	Soil	0,0699 mg/kg	Marine water	0,04 mg/L
EC: 201-148-0	Intermittent	11 mg/L	Sediment (Fresh water)	1,52 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,152 mg/kg

#### 8.2 **Exposure controls:**

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

#### B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Revised: 19/03/2020



### MORAVIA - MORAMASTIC 8303 (COMPONENT A) AS16-8303A

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued) Pictogram PPE Labelling **CEN Standard** Remarks The Breakthrough Time indicated by the EN ISO 374-1:2016 manufacturer must exceed the period during which NON-disposable chemical EN 16523-1:2015 the product is being used. Do not use protective protective gloves EN 420:2003+A1:2009 creams after the product has come into contact **CAT III** Mandatory hand with skin. protection "As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application" D.- Ocular and facial protection **CEN** Standard Pictogram PPE Labelling Remarks EN 166:2001 Clean daily and disinfect periodically according to EN 167:2001 Face shield the manufacturer's instructions. Use if there is a FN 168:2001 risk of splashing. EN ISO 4007:2018 Mandatory face CAT II protection E.- Body protection PPE Labelling CEN Standard Remarks Pictogram EN 1149-1.2.3 EN 13034:2005+A1:2009 Disposable clothing for EN ISO 13982protection against chemical 1:2004/A1:2010 For professional use only. Clean periodically risks, with antistatic and EN ISO 6529:2013 according to the manufacturer's instructions. Mandatory complete CAT III fireproof properties EN ISO 6530:2005 body protection EN ISO 13688:2013 EN 464:1994 Safety footwear for EN ISO 13287:2012 protection against chemical EN ISO 20345:2011 Replace boots at any sign of deterioration. risk, with antistatic and heat EN 13832-1:2019 resistant properties Mandatory foot CAT III protection F.- Additional emergency measures Emergency measure Standards Emergency measure Standards **@**+ ANSI Z358-1 DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 ISO 3864-1:2011, ISO 3864-4:2011 Eyewash stations Emergency shower **Environmental exposure controls:** In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D Volatile organic compounds: With regard to Directive 2010/75/EU, this product has the following characteristics: V.O.C. (Supply): 16,13 % weight 240,26 kg/m3 (240,26 g/L) V.O.C. density at 20 °C: Average carbon number: 7,46 Average molecular weight: 107,39 g/mol SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES Information on basic physical and chemical properties: 9.1 For complete information see the product datasheet. Appearance: Physical state at 20 °C: Liquid Appearance: Not available Colour: Silver

\*Not relevant due to the nature of the product, not providing information property of its hazards.



SEC	TION 9: PHYSICAL AND CHEMICAL PROPERTIES	(continued)
	Odour:	Not available
	Odour threshold:	Non-applicable *
	Volatility:	
	Boiling point at atmospheric pressure:	130 °C
	Vapour pressure at 20 °C:	903 Pa
	Vapour pressure at 50 °C:	5311,16 Pa (5,31 kPa)
	Evaporation rate at 20 °C:	Non-applicable *
	Product description:	
	Density at 20 °C:	1460 - 1520 kg/m³
	Relative density at 20 °C:	1,46 - 1,52
	Dynamic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 40 °C:	Non-applicable *
	Concentration:	Non-applicable *
	pH:	Non-applicable *
	Vapour density at 20 °C:	Non-applicable *
	Partition coefficient n-octanol/water 20 °C:	Non-applicable *
	Solubility in water at 20 °C:	Non-applicable *
	Solubility properties:	Non-applicable *
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Flammability:	
	Flash Point:	28 °C
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	230 °C
	Lower flammability limit:	Not available
	Upper flammability limit:	Not available
	Explosive:	
	Lower explosive limit:	Non-applicable *
	Upper explosive limit:	Non-applicable *
9.2	Other information:	
	Surface tension at 20 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providing inform	nation property of its hazards.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

### **10.3** Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4** Conditions to avoid:



	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
	Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable
).5 Ir	compatible materials:				
	Acids	Water	Oxidising materials	Combustible materials	Others
	Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bas
cc	mplex mixtures of chemic mpounds. N 11: TOXICOLOGICA		eleased: carbon dioxide (CO		decomposition conditior l other organic
cc ECTIO	mpounds.	AL INFORMATION	eleased: carbon dioxide (CO		
cc ECTIO 1.1 Ir	mpounds. N 11: TOXICOLOGICA	AL INFORMATION	eleased: carbon dioxide (CO	2), carbon monoxide and	l other organic
CC ECTIO L1.1 Ir Tł	mpounds. N 11: TOXICOLOGICA	AL INFORMATION gical effects: on related to the toxicol		2), carbon monoxide and	l other organic
ECTIO	mpounds. N 11: TOXICOLOGICA formation on toxicological me experimental information angerous health implicant case of exposure that is	AL INFORMATION gical effects: on related to the toxicol cations: repetitive, prolonged or nay result, depending or		2), carbon monoxide and	l other organic

- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
  - Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
  - IARC: Talc (3); Xylene (3)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- Skin: Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.



### MORAVIA - MORAMASTIC 8303 (COMPONENT A) AS16-8303A

### SECTION 11: TOXICOLOGICAL INFORMATION (continued)

### H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

### Other information:

### Non-applicable

### Specific toxicology information on the substances:

Identification	Ad	cute toxicity	Genus
2-methylpropan-1-ol	LD50 oral	3350 mg/kg	Rat
CAS: 78-83-1	LD50 dermal	2460 mg/kg	Rabbit
EC: 201-148-0	LC50 inhalation	24,6 mg/L (4 h)	Rat
Xylene	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg (ATEi)	Rat
EC: 215-535-7	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Solvent naphtha (petroleum), medium aliph.	LD50 oral	5100 mg/kg	Rat
CAS: 64742-88-7	LD50 dermal	Non-applicable	
EC: 265-191-7	LC50 inhalation	Non-applicable	

### SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

### 12.1 Toxicity:

Identification		Acute toxicity	Species	Genus
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 )	LC50	1 - 10 mg/L (96 h)		Fish
CAS: 25068-38-6	EC50	1 - 10 mg/L		Crustacean
EC: 500-033-5	EC50	1 - 10 mg/L		Algae
Xylene	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 1330-20-7	EC50	3.4 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
EC: 215-535-7	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
Phenol, methylstyrenated	LC50	10 - 100 mg/L (96 h)		Fish
CAS: 68512-30-1	EC50	10 - 100 mg/L		Crustacean
EC: 270-966-8	EC50	10 - 100 mg/L		Algae
2-methylpropan-1-ol	LC50	2030 mg/L (96 h)	Carassius auratus	Fish
CAS: 78-83-1	EC50	1439 mg/L (48 h)	Daphnia magna	Crustacean
EC: 201-148-0	EC50	1250 mg/L (48 h)	Scenedesmus subspicatus	Algae
Solvent naphtha (petroleum), medium aliph.	LC50	1 - 10 mg/L (96 h)		Fish
CAS: 64742-88-7	EC50	1 - 10 mg/L		Crustacean
EC: 265-191-7	EC50	1 - 10 mg/L		Algae

### 12.2 Persistence and degradability:

Identification	Degra	adability	Biodegradab	ility
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 )	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 25068-38-6	COD	Non-applicable	Period	28 days
EC: 500-033-5	BOD5/COD	Non-applicable	% Biodegradable	0 %
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %
2-methylpropan-1-ol	BOD5	0.4 g O2/g	Concentration	100 mg/L
CAS: 78-83-1	COD	2.41 g O2/g	Period	14 days
EC: 201-148-0	BOD5/COD	0.17	% Biodegradable	90 %
Bioaccumulative potential:				

Revised: 19/03/2020



### MORAVIA - MORAMASTIC 8303 (COMPONENT A) AS16-8303A

### SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification		Bioaccumulation potential		
reaction product: bisphenol-A-(epichlorhydrin) ( MW < 700 )		BCF	4	
CAS: 25068-38-6		Pow Log	2.8	
EC: 500-033-5		Potential	Low	
Xylene		BCF	9	
CAS: 1330-20-7		Pow Log	2.77	
EC: 215-535-7		Potential	Low	
2-methylpropan-1-ol		BCF	3	
CAS: 78-83-1 EC: 201-148-0		Pow Log	0.76	
		Potential	Low	
Solvent naphtha (petroleum), medium aliph.		BCF		
CAS: 64742-88-7		Pow Log	4.6	
EC: 265-191-7		Potential		

### 12.4 Mobility in soil:

Identification	Absorpt	Absorption/desorption		Volatility	
Xylene	Кос	202	Henry	524,86 Pa·m <sup>3</sup> /mol	
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes	
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes	
2-methylpropan-1-ol	Кос	Non-applicable	Henry	Non-applicable	
CAS: 78-83-1	Conclusion	Non-applicable	Dry soil	Non-applicable	
EC: 201-148-0	Surface tension	2,378E-2 N/m (25 °C)	Moist soil	Non-applicable	

### 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

#### 12.6 Other adverse effects:

Not described

### SECTION 13: DISPOSAL CONSIDERATIONS

#### **13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

#### Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

### **Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

### SECTION 14: TRANSPORT INFORMATION

### Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:



SECTION 14: TRANSPORT	INFORMATION (continued)	
14.1	UN number:	UN1263
	2 UN proper shipping name:	PAINT
	Transport hazard class(es):	3
	Labels:	3
14.4	Packing group:	III
	Environmental hazards:	Yes
14.6	Special precautions for user	
	Special regulations:	163, 367, 650
	Tunnel restriction code:	D/E
	Physico-Chemical properties:	see section 9 5 L
14.7	Limited quantities: <b>Transport in bulk according</b>	S L Non-applicable
14.7	to Annex II of Marpol and	Non-applicable
	the IBC Code:	
Transport of danger	ous goods by sea:	
With regard to IMDG 3	9-18:	
14.1	UN number:	UN1263
<b>14.</b> 2	2 UN proper shipping name:	PAINT
14.3	Transport hazard class(es):	3
3	Labels:	3
	Packing group:	III
	Environmental hazards:	Yes
14.6	Special precautions for user	
	Special regulations:	223, 955, 163, 367
	EmS Codes:	F-E, S-E see section 9
	Physico-Chemical properties: Limited quantities:	5 L
	Segregation group:	Non-applicable
14.7	<ul> <li>Transport in bulk according</li> </ul>	Non-applicable
	to Annex II of Marpol and	
	the IBC Code:	
Transport of danger		
With regard to IATA/IO	CAO 2020:	
	UN number:	UN1263
	2 UN proper shipping name:	PAINT
🔻 🗸 14.3	Transport hazard class(es):	3
	Labels:	3
	Packing group: Environmental hazards:	III Yes
	Special precautions for user	
14.0	Physico-Chemical properties:	see section 9
14.7	<ul> <li>Transport in bulk according</li> </ul>	Non-applicable
	to Annex II of Marpol and	
	the IBC Code:	
L		

## SECTION 15: REGULATORY INFORMATION

	15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:			
	Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable			
	Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable			
	Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable			
	Article 95, REGULATION (EU) No 528/2012: Non-applicable			
	REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable			
	Seveso III:			
L	- CONTINUED ON NEXT PAGE -			



### MORAVIA - MORAMASTIC 8303 (COMPONENT A) AS16-8303A

### SECTION 15: REGULATORY INFORMATION (continued)

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c		5000	50000
E2		200	500
Limitations to commencialization and the use of contain demonstrate substances and mintures (Amere XV/TT DEACU			

# Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

metallic glitter intended mainly for decoration,

artificial snow and frost,

- "whoopee" cushions,

- silly string aerosols,
- imitation excrement,
- horns for parties,

- decorative flakes and foams,

artificial cobwebs,

— stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

### Other legislation:

The product could be affected by sectorial legislation

### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

### SECTION 16: OTHER INFORMATION

### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

#### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: Non-applicable

Non-applicable

### Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation

H318: Causes serious eye damage

H317: May cause an allergic skin reaction

H411: Toxic to aquatic life with long lasting effects

H312+H332: Harmful in contact with skin or if inhaled

H226: Flammable liquid and vapour

### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

### CLP Regulation (EC) No 1272/2008:



### MORAVIA - MORAMASTIC 8303 (COMPONENT A) AS16-8303A

### SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways Eye Dam. 1: H318 - Causes serious eye damage Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 3: H226 - Flammable liquid and vapour Skin Irrit. 2: H315 - Causes skin irritation Skin Sens. 1: H317 - May cause an allergic skin reaction STOT SE 3: H335 - May cause drowsiness or dizziness **Classification procedure:** 

Skin Irrit. 2: Calculation method Eye Dam. 1: Calculation method Skin Sens. 1: Calculation method Aquatic Chronic 2: Calculation method Acute Tox. 4: Calculation method Flam. Liq. 3: Calculation method (2.6.4.3)

#### Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

### Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

### Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5-day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LC50: Lethal Concentration 50 LC50: Chemical oxygen partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -