

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier: MORAVIA - MORAHOLD SK01-0121

## **1.2** Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Paint. For professional user/industrial user only.

Uses advised against: All uses not specified in this section or in section 7.3

## **1.3** Details of the supplier of the safety data sheet:

MORAVİA BOYA VE KİMYA SAN.TİC.LTD.ŞTİ FEVZİ ÇAKMAK CADDESİ NO:2 SEFAKÖY/ KÜÇÜKÇEKMECE İSTANBUL - TURKEY Phone.: +90 212 579 13 36 - Fax: +90 212 426 55 12 moravia@moravia.com.tr www.moravia.com.tr

#### 1.4 Emergency telephone number:

## SECTION 2: HAZARDS IDENTIFICATION \*\*

## 2.1 Classification of the substance or mixture:

## CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411

Asp. Tox. 1: Aspiration hazard, Category 1, H304 Flam. Liq. 3: Flammable liquids, Category 3, H226 Repr. 1B: Reproductive toxicity, Category 1B, H360 Skin Irrit. 2: Skin irritation, Category 2, H315 Skin Sens. 1A: Sensitisation, skin, Category 1A, H317 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

#### 2.2 Label elements:

#### CLP Regulation (EC) No 1272/2008:

Danger



#### Hazard statements:

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways Flam. Liq. 3: H226 - Flammable liquid and vapour Repr. 1B: H360 - May damage fertility or the unborn child Skin Irrit. 2: H315 - Causes skin irritation Skin Sens. 1A: H317 - May cause an allergic skin reaction STOT SE 3: H336 - May cause drowsiness or dizziness **Precautionary statements:** P201: Obtain special instructions before use

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280: Wear protective gloves/protective clothing/eye protection/face protection

P302+P352: IF ON SKIN: Wash with plenty of water

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing

P308+P313: IF exposed or concerned: Get medical advice/attention

P370+P378: In case of fire: Use ABC powder extinguisher to extinguish

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively

## Supplementary information:

Contains 2-butanone oxime

#### Substances that contribute to the classification

\*\* Changes with regards to the previous version



# SECTION 2: HAZARDS IDENTIFICATION \*\* (continued)

Solvent naphtha (petroleum), medium aliph.; Hydrocarbons, C9-unsaturated, polymerised; Toluene; Cobalt bis(2-ethylhexanoate) Additional Labelling (Annex XVII, REACH):

Restricted to professional users

# 2.3 Other hazards:

# Product fails to meet PBT/vPvB criteria

\*\* Changes with regards to the previous version

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.1 Substance:

Non-applicable

# 3.2 Mixture:

## Chemical description: Miscellaneous products

## Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification		Concentration
CAS: EC:	64742-88-7 265-191-7	Solvent naphtha (pe	troleum), medium aliph. <sup>(1)</sup>	Self-classified	
Index:	649-405-00-X 01-2119537181-47- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H336; EUH066 - Danger	! 🔅 🚯 😩	10 - <25 %
CAS: EC:	71302-83-5 615-276-3	Hydrocarbons, C9-u	nsaturated, polymerised <sup>(1)</sup>	Self-classified	
Index:		Regulation 1272/2008	Aquatic Chronic 3: H412; Skin Sens. 1A: H317 - Warning		2,5 - <10 %
CAS:	108-88-3	Toluene <sup>(1)</sup>		ATP CLP00	
	203-625-9 601-021-00-3 01-2119471310-51- XXXX	Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	() (8) (8)	1 - <2,5 %
CAS:	7779-90-0	trizinc bis(orthophos	sphate) <sup>(1)</sup>	ATP CLP00	
EC: 231-944-3 Index: Non-applicable REACH: 01-2119485044 XXXX	Non-applicable 01-2119485044-40-	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning	×.	<1 %
CAS:	136-52-7 205-250-6 Non-applicable 01-2119524678-29- XXXX	Cobalt bis(2-ethylhe	Self-classified		
Index: Nor REACH: 01-		Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Repr. 1B: H360; Skin Sens. 1A: H317 - Danger	(Ì) 🚯 😩	<1 %
CAS:	96-29-7	2-butanone oxime <sup>(1)</sup>	)	ATP CLP00	
	202-496-6 616-014-00-0 01-2119539477-28- XXXX	Regulation 1272/2008	Acute Tox. 4: H312; Carc. 2: H351; Eye Dam. 1: H318; Skin Sens. 1: H317 - Danger	(1) (2) (3)	<1 %
CAS:	22464-99-9	245-018-1 Non-applicable 01-2119979088-21- Regulation 1272/2008 Repr. 2: H361d - Warning	l, zirconium salt <sup>(1)</sup>	Self-classified	
			Repr. 2: H361d - Warning	٠	<1 %
CAS:	1330-20-7	Xylene <sup>(2)</sup>		ATP CLP00	
	215-535-7 601-022-00-9 01-2119488216-32- XXXX	Regulation 1272/2008	Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	() ()	<1 %
CAS:	1314-13-2	zinc oxide <sup>(1)</sup>		ATP CLP00	
	215-222-5 030-013-00-7 01-2119463881-32- XXXX	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning		<1 %



## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

	Identification		Chemical name/Classification C			
CAS:	136-51-6	calcium bis(2-ethylh	exanoate) <sup>(1)</sup>	Self-classified		
EC: 205-249-0 Index: Non-applicable REACH: 01-2119978297-19- XXXX	Regulation 1272/2008	Eye Dam. 1: H318; Repr. 2: H361d - Danger		<1 %		

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830 <sup>(2)</sup> Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

## SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

## By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

## By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

#### By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

## 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

## 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

## SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

## 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

## Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.



# SECTION 6: ACCIDENTAL RELEASE MEASURES

## 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

#### 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

## 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

# 6.4 Reference to other sections:

See sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

## 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

## 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:	5 °C
Maximum Temp.:	30 °C
Maximum time:	6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

## 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Revised: 09/06/2020

#### 8.1 Control parameters:



# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

## Substances whose occupational exposure limits have to be monitored in the workplace

	Identification	Occupational exposure limits			
Toluene		IOELV (8h)	50 ppm	192 mg/m <sup>3</sup>	
CAS: 108-88-3	EC: 203-625-9	IOELV (STEL)	100 ppm	384 mg/m <sup>3</sup>	
Xylene		IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>	
CAS: 1330-20-7	EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>	

## DNEL (Workers):

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Toluene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	384 mg/m <sup>3</sup>	384 mg/m <sup>3</sup>	192 mg/m <sup>3</sup>	192 mg/m <sup>3</sup>
trizinc bis(orthophosphate)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 7779-90-0	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 231-944-3	Inhalation	Non-applicable	Non-applicable	5 mg/m <sup>3</sup>	Non-applicable
Cobalt bis(2-ethylhexanoate)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 136-52-7	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 205-250-6	Inhalation	Non-applicable	Non-applicable	Non-applicable	0,2351 mg/m <sup>3</sup>
2-butanone oxime	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 96-29-7	Dermal	2,5 mg/kg	Non-applicable	1,3 mg/kg	Non-applicable
EC: 202-496-6	Inhalation	Non-applicable	Non-applicable	9 mg/m <sup>3</sup>	3,33 mg/m <sup>3</sup>
2-ethylhexanoic acid, zirconium salt	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 22464-99-9	Dermal	Non-applicable	Non-applicable	15,75 mg/kg	Non-applicable
EC: 245-018-1	Inhalation	Non-applicable	Non-applicable	5 mg/m <sup>3</sup>	Non-applicable
Xylene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
EC: 215-535-7	Inhalation	289 mg/m <sup>3</sup>	289 mg/m <sup>3</sup>	77 mg/m <sup>3</sup>	Non-applicable
zinc oxide	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 1314-13-2	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 215-222-5	Inhalation	Non-applicable	Non-applicable	5 mg/m <sup>3</sup>	Non-applicable
calcium bis(2-ethylhexanoate)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 136-51-6	Dermal	Non-applicable	Non-applicable	5,67 mg/kg	Non-applicable
EC: 205-249-0	Inhalation	Non-applicable	Non-applicable	39,98 mg/m <sup>3</sup>	Non-applicable

## DNEL (General population):

		Short e	xposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Toluene	Oral	Non-applicable	Non-applicable	8,13 mg/kg	Non-applicable
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable
EC: 203-625-9	Inhalation	226 mg/m <sup>3</sup>	226 mg/m <sup>3</sup>	56,5 mg/m³	56,5 mg/m <sup>3</sup>
trizinc bis(orthophosphate)	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable
CAS: 7779-90-0	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
EC: 231-944-3	Inhalation	Non-applicable	Non-applicable	2,5 mg/m <sup>3</sup>	Non-applicable
Cobalt bis(2-ethylhexanoate)	Oral	Non-applicable	Non-applicable	0,0558 mg/kg	Non-applicable
CAS: 136-52-7	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 205-250-6	Inhalation	Non-applicable	Non-applicable	Non-applicable	0,037 mg/m <sup>3</sup>
2-butanone oxime	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 96-29-7	Dermal	1,5 mg/kg	Non-applicable	0,78 mg/kg	Non-applicable
EC: 202-496-6	Inhalation	Non-applicable	Non-applicable	2,7 mg/m <sup>3</sup>	2 mg/m <sup>3</sup>
2-ethylhexanoic acid, zirconium salt	Oral	Non-applicable	Non-applicable	7,9 mg/kg	Non-applicable
CAS: 22464-99-9	Dermal	Non-applicable	Non-applicable	7,9 mg/kg	Non-applicable
EC: 245-018-1	Inhalation	Non-applicable	Non-applicable	2,5 mg/m³	Non-applicable



# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	exposure	Lo	ong exposure	
Identification		Systemic	Local	Systemic	: Local	
Xylene	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable	
CAS: 1330-20-7	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable	
EC: 215-535-7	Inhalation	Non-applicable	Non-applicable	14,8 mg/m <sup>3</sup>	Non-applicable	
zinc oxide	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable	
CAS: 1314-13-2	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable	
EC: 215-222-5	Inhalation	Non-applicable	Non-applicable	2,5 mg/m <sup>3</sup>	Non-applicable	
calcium bis(2-ethylhexanoate)	Oral	Non-applicable	Non-applicable	2,83 mg/kg	Non-applicable	
CAS: 136-51-6	Dermal	Non-applicable	Non-applicable	2,83 mg/kg	Non-applicable	
EC: 205-249-0	Inhalation	Non-applicable	Non-applicable	9,86 mg/m <sup>3</sup>	Non-applicable	
PNEC:	•	•				
Identification						
Toluene	STP	13,61 mg/L	Fresh water		0,68 mg/L	
CAS: 108-88-3	Soil	2,89 mg/kg	Marine water		0,68 mg/L	
EC: 203-625-9	Intermittent	0,68 mg/L	Sediment (Fresh	water)	16,39 mg/kg	
	Oral	Non-applicable	Sediment (Marin	ie water)	16,39 mg/kg	
trizinc bis(orthophosphate)	STP	0,1 mg/L	Fresh water		0,0206 mg/L	
CAS: 7779-90-0	Soil	35,6 mg/kg	Marine water		0,0061 mg/L	
EC: 231-944-3	Intermittent	Non-applicable	Sediment (Fresh	water)	117,8 mg/kg	
	Oral	Non-applicable	Sediment (Marin	ie water)	56,5 mg/kg	
Cobalt bis(2-ethylhexanoate)	STP	0,37 mg/L	Fresh water	Fresh water		
CAS: 136-52-7	Soil	7,9 mg/kg	Marine water		0,00236 mg/L	
EC: 205-250-6	Intermittent	Non-applicable	Sediment (Fresh	ı water)	9,5 mg/kg	
	Oral	Non-applicable	Sediment (Marin	ie water)	9,5 mg/kg	
2-butanone oxime	STP	177 mg/L	Fresh water		0,256 mg/L	
CAS: 96-29-7	Soil	Non-applicable	Marine water		Non-applicable	
EC: 202-496-6	Intermittent	0,118 mg/L	Sediment (Fresh	water)	Non-applicable	
	Oral	Non-applicable	Sediment (Marin	ie water)	Non-applicable	
2-ethylhexanoic acid, zirconium salt	STP	71,7 mg/L	Fresh water		0,36 mg/L	
CAS: 22464-99-9	Soil	1,06 mg/kg	Marine water		0,036 mg/L	
EC: 245-018-1	Intermittent	0,493 mg/L	Sediment (Fresh	ı water)	6,37 mg/kg	
	Oral	Non-applicable	Sediment (Marin	ie water)	0,637 mg/kg	
Xylene	STP	6,58 mg/L	Fresh water		0,327 mg/L	
CAS: 1330-20-7	Soil	2,31 mg/kg	Marine water		0,327 mg/L	
EC: 215-535-7	Intermittent	0,327 mg/L	Sediment (Fresh		12,46 mg/kg	
	Oral	Non-applicable	Sediment (Marin	e water)	12,46 mg/kg	
zinc oxide	STP	0,1 mg/L	Fresh water		0,0206 mg/L	
CAS: 1314-13-2	Soil	35,6 mg/kg	Marine water		0,0061 mg/L	
EC: 215-222-5	Intermittent	Non-applicable	Sediment (Fresh	· · ·	117,8 mg/kg	
	Oral	Non-applicable	Sediment (Marin	e water)	56,5 mg/kg	
calcium bis(2-ethylhexanoate)	STP	71,7 mg/L	Fresh water		0,36 mg/L	
CAS: 136-51-6	Soil	1,06 mg/kg	Marine water		0,036 mg/L	
EC: 205-249-0	Intermittent	0,493 mg/L	Sediment (Fresh		6,37 mg/kg	
	Oral	Non-applicable	Sediment (Marin	ie water)	0,637 mg/kg	

## 8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



	Pictogram	PF	ΡĒ	Labelling		CEN Standard		Remarks
	Mandatory respiratory tract protection	Filter mask fo vapo			EN	405:2001+A1:2009		lace when there is a taste or smell of the ontaminant inside the face mask. If the contaminant comes with warnings it is commended to use isolation equipment.
C	Specific protection	n for the han	ds					
	Pictogram	PF	Έ	Labelling		CEN Standard		Remarks
	Mandatory hand protection	NON-disposa protectiv			E	N ISO 374-1:2016 EN 16523-1:2015 420:2003+A1:2009	manufa the p	he Breakthrough Time indicated by the acturer must exceed the period during wh roduct is being used. Do not use protectiv ns after the product has come into contac with skin.
							erial ca	n not be predicted in advance with
	total reliability and Ocular and facial		re to be che	cked prior to th	ne appl	lication"		
U			-					
	Pictogram	PF	Ϋ́Ε	Labelling		CEN Standard		Remarks
	Mandatory face protection	Face s	shield		E	EN 166:2001 EN 167:2001 EN 168:2001 N ISO 4007:2018	Clean the m	daily and disinfect periodically according anufacturer's instructions. Use if there is risk of splashing.
E	Body protection							
	Pictogram	PF	Έ	Labelling		CEN Standard		Remarks
	Mandatory complete body protection	Disposable protection aga risks, with a fireproof p	ninst chemical ntistatic and		E	EN 1149-1,2,3 3034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 N ISO 6529:2013 N ISO 6530:2005 V ISO 13688:2013 EN 464:1994		professional use only. Clean periodically ording to the manufacturer's instructions.
	Mandatory foot protection	Safety foc protection aga risk, with antis resistant p	ainst chemical tatic and heat		Eľ	N ISO 13287:2012 N ISO 20345:2011 EN 13832-1:2019	Re	place boots at any sign of deterioration.
F	Additional emerge	ency measure	es					
	Emergency mea	asure	St	andards		Emergency measure	ure	Standards
	Emergency sho			5I Z358-1 11, ISO 3864-4:20	11	Eyewash station		DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

spillage of both the product and its container. For additional information see subsection 7.1.D

## Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	26,05 % weight
V.O.C. density at 20 °C:	351,68 kg/m <sup>3</sup> (351,68 g/L)
Average carbon number:	9,8
Average molecular weight:	152,52 g/mol

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

\*Not relevant due to the nature of the product, not providing information property of its hazards.



SECT	TION 9: PHYSICAL AND CHEMICAL PROPER	RTIES (continued)
9.1	Information on basic physical and chemica	l properties:
	For complete information see the product datash	eet.
	Appearance:	
	Physical state at 20 °C:	Liquid
	Appearance:	Not available
	Colour:	Several
	Odour:	Not available
	Odour threshold:	Non-applicable *
	Volatility:	
	Boiling point at atmospheric pressure:	141 °C
	Vapour pressure at 20 °C:	611 Pa
	Vapour pressure at 50 °C:	3628,01 Pa (3,63 kPa)
	Evaporation rate at 20 °C:	Non-applicable *
	Product description:	
	Density at 20 °C:	1320 - 1380 kg/m³
	Relative density at 20 °C:	1,32 - 1,38
	Dynamic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 40 °C:	<20,5 cSt
	Concentration:	Non-applicable *
	pH:	Non-applicable *
	Vapour density at 20 °C:	Non-applicable *
	Partition coefficient n-octanol/water 20 °C:	Non-applicable *
	Solubility in water at 20 °C:	Non-applicable *
	Solubility properties:	Non-applicable *
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Flammability:	
	Flash Point:	39 °C
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	230 °C
	Lower flammability limit:	Not available
	Upper flammability limit:	Not available
	Explosive:	
	Lower explosive limit:	Non-applicable *
	Upper explosive limit:	Non-applicable *
9.2	Other information:	
	Surface tension at 20 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providin	g information property of its hazards.

# SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:



## SECTION 10: STABILITY AND REACTIVITY (continued)

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

## **10.2** Chemical stability:

Chemically stable under the conditions of storage, handling and use.

## **10.3** Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### **10.4** Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

#### **10.5** Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

#### **10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

## Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
  - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
  - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
    - IARC: Xylene (3); Toluene (3)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Reproductive toxicity: May damage fertility or the unborn child
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.



# SECTION 11: TOXICOLOGICAL INFORMATION (continued)

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

- Skin: Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

#### Other information:

Non-applicable

## Specific toxicology information on the substances:

Identification	Ac	ute toxicity	Genus
Toluene	LD50 oral	5580 mg/kg	Rat
CAS: 108-88-3	LD50 dermal	12124 mg/kg	Rat
EC: 203-625-9	LC50 inhalation	28,1 mg/L (4 h)	Rat
Solvent naphtha (petroleum), medium aliph.	LD50 oral	5100 mg/kg	Rat
CAS: 64742-88-7	LD50 dermal	Non-applicable	
EC: 265-191-7	LC50 inhalation	Non-applicable	
2-butanone oxime	LD50 oral	2100 mg/kg	Rat
CAS: 96-29-7	LD50 dermal	1100 mg/kg	Rat
EC: 202-496-6	LC50 inhalation	Non-applicable	
2-ethylhexanoic acid, zirconium salt	LD50 oral	2043 mg/kg	Rat
CAS: 22464-99-9	LD50 dermal	Non-applicable	
EC: 245-018-1	LC50 inhalation	Non-applicable	
Xylene	LD50 oral	2100 mg/kg	Rat
CAS: 1330-20-7	LD50 dermal	1100 mg/kg	Rat
EC: 215-535-7	LC50 inhalation	Non-applicable	
zinc oxide	LD50 oral	7950 mg/kg	Mouse
CAS: 1314-13-2	LD50 dermal	Non-applicable	
EC: 215-222-5	LC50 inhalation	Non-applicable	
calcium bis(2-ethylhexanoate)	LD50 oral	2043 mg/kg	Rat
CAS: 136-51-6	LD50 dermal	Non-applicable	
EC: 205-249-0	LC50 inhalation	Non-applicable	

## SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

#### 12.1 Toxicity:

Identification		Acute toxicity	Species	Genus
Solvent naphtha (petroleum), medium aliph.	LC50	1 - 10 mg/L (96 h)		Fish
CAS: 64742-88-7	EC50	1 - 10 mg/L		Crustacean
EC: 265-191-7	EC50	1 - 10 mg/L		Algae
Hydrocarbons, C9-unsaturated, polymerised	LC50	10 - 100 mg/L (96 h)		Fish
CAS: 71302-83-5	EC50	10 - 100 mg/L		Crustacean
EC: 615-276-3	EC50	10 - 100 mg/L		Algae
Toluene	LC50	13 mg/L (96 h)	Carassius auratus	Fish
CAS: 108-88-3	EC50	11.5 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-625-9	EC50	125 mg/L (48 h)	Scenedesmus subspicatus	Algae



## Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

# MORAVIA - MORAHOLD SK01-0121

# SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification		Acute toxicity	Species	Genus
trizinc bis(orthophosphate)	LC50	0.1 - 1 mg/L (96 h)		Fish
CAS: 7779-90-0	EC50	0.1 - 1 mg/L		Crustacean
EC: 231-944-3	EC50	0.1 - 1 mg/L		Algae
Cobalt bis(2-ethylhexanoate)	LC50	0.1 - 1 mg/L (96 h)		Fish
CAS: 136-52-7	EC50	0.1 - 1 mg/L		Crustacean
EC: 205-250-6	EC50	0.1 - 1 mg/L		Algae
2-butanone oxime	LC50	843 mg/L (96 h)	Pimephales promelas	Fish
CAS: 96-29-7	EC50	750 mg/L (48 h)	Daphnia magna	Crustacean
EC: 202-496-6	EC50	83 mg/L (72 h)	Scenedesmus subspicatus	Algae
2-ethylhexanoic acid, zirconium salt	LC50	270 mg/L (96 h)	N/A	Fish
CAS: 22464-99-9	EC50	Non-applicable		
EC: 245-018-1	EC50	Non-applicable		
Xylene	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 1330-20-7	EC50	3.4 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
EC: 215-535-7	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
zinc oxide	LC50	0.82 mg/L (96 h)	Oncorhynchus kisutch	Fish
CAS: 1314-13-2	EC50	3.4 mg/L (48 h)	Daphnia magna	Crustacean
EC: 215-222-5	EC50	Non-applicable		
calcium bis(2-ethylhexanoate)	LC50	270 mg/L (96 h)	N/A	Fish
CAS: 136-51-6	EC50	Non-applicable		
EC: 205-249-0	EC50	Non-applicable		

# 12.2 Persistence and degradability:

Identification	Degr	adability	Biodegradab	ility
Toluene	BOD5	2.5 g O2/g	Concentration	100 mg/L
CAS: 108-88-3	COD	Non-applicable	Period	14 days
EC: 203-625-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
2-butanone oxime	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 96-29-7	COD	Non-applicable	Period	28 days
EC: 202-496-6	BOD5/COD	Non-applicable	% Biodegradable	24 %
2-ethylhexanoic acid, zirconium salt	BOD5	Non-applicable	Concentration	20 mg/L
CAS: 22464-99-9	COD	Non-applicable	Period	28 days
EC: 245-018-1	BOD5/COD	Non-applicable	% Biodegradable	99 %
Xylene	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1330-20-7	COD	Non-applicable	Period	28 days
EC: 215-535-7	BOD5/COD	Non-applicable	% Biodegradable	88 %
calcium bis(2-ethylhexanoate)	BOD5	Non-applicable	Concentration	20 mg/L
CAS: 136-51-6	COD	Non-applicable	Period	28 days
EC: 205-249-0	BOD5/COD	Non-applicable	% Biodegradable	99 %

## **12.3** Bioaccumulative potential:

Identification		Bioaccumulation potential		
Solvent naphtha (petroleum), medium aliph.	BCF	:		
CAS: 64742-88-7	Pow	/ Log	4.6	
EC: 265-191-7	Pote	ential		
Toluene	BCF	:	13	
CAS: 108-88-3	Pow	/ Log	2.73	
EC: 203-625-9	Pote	ential	Low	
2-butanone oxime	BCF	:	5	
CAS: 96-29-7	Pow	/ Log	0.59	
EC: 202-496-6	Pote	ential	Low	
2-ethylhexanoic acid, zirconium salt	BCF	:		
CAS: 22464-99-9	Pow	/ Log	2.96	
EC: 245-018-1	Pote	ential		



## SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification		Bioaccumulation potential	
Xylene	BCF	9	
CAS: 1330-20-7	Pow Log	2.77	
EC: 215-535-7	Potential	Low	
calcium bis(2-ethylhexanoate)	BCF		
CAS: 136-51-6	Pow Log	2.96	
EC: 205-249-0	Potential		

## 12.4 Mobility in soil:

Identification	Absorp	tion/desorption		Volatility
Toluene	Кос	178	Henry	672,8 Pa·m <sup>3</sup> /mol
CAS: 108-88-3	Conclusion	Moderate	Dry soil	Yes
EC: 203-625-9	Surface tension	2,793E-2 N/m (25 °C)	Moist soil	Yes
2-butanone oxime	Кос	3	Henry	Non-applicable
CAS: 96-29-7	Conclusion	Very High	Dry soil	Non-applicable
EC: 202-496-6	Surface tension	2,57E-2 N/m (25 °C)	Moist soil	Non-applicable
2-ethylhexanoic acid, zirconium salt	Кос	Non-applicable	Henry	2,94E-1 Pa·m <sup>3</sup> /mol
CAS: 22464-99-9	Conclusion	Non-applicable	Dry soil	Yes
EC: 245-018-1	Surface tension	Non-applicable	Moist soil	Yes
Xylene	Кос	202	Henry	524,86 Pa·m <sup>3</sup> /mol
CAS: 1330-20-7	Conclusion	Moderate	Dry soil	Yes
EC: 215-535-7	Surface tension	Non-applicable	Moist soil	Yes
calcium bis(2-ethylhexanoate)	Кос	Non-applicable	Henry	2,94E-1 Pa·m <sup>3</sup> /mol
CAS: 136-51-6	Conclusion	Non-applicable	Dry soil	Yes
EC: 205-249-0	Surface tension	Non-applicable	Moist soil	Yes

# **12.5** Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

## **12.6** Other adverse effects:

Not described

## SECTION 13: DISPOSAL CONSIDERATIONS

## **13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

#### Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable, HP10 Toxic for reproduction, HP4 Irritant — skin irritation and eye damage

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

## **Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

## SECTION 14: TRANSPORT INFORMATION

## Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:



SECTION 14: TRANSPORT	INFORMATION (continued)	
1/1	UN number:	UN1263
	UN proper shipping name:	PAINT
	Transport hazard class(es):	3
3	Labels:	3
14.4	Packing group:	III
	Environmental hazards:	Yes
	Special precautions for user	
	Special regulations:	163, 367, 650
	Tunnel restriction code:	D/E
	Physico-Chemical properties:	see section 9
	Limited quantities:	5 L
14.7	Transport in bulk according	Non-applicable
	to Annex II of Marpol and	
-	the IBC Code:	
Transport of dangero		
With regard to IMDG 39		
	UN number:	UN1263
	UN proper shipping name:	PAINT
	Transport hazard class(es):	3
	Labels:	3
	Packing group:	III
	Environmental hazards:	Yes
14.6	Special precautions for user	
	Special regulations:	223, 955, 163, 367
	EmS Codes:	F-E, S-E
	Physico-Chemical properties:	see section 9
	Limited quantities:	5 L Non annliashla
147	Segregation group:	Non-applicable
14.7	Transport in bulk according to Annex II of Marpol and	Non-applicable
	the IBC Code:	
Transport of dangero	us goods by air:	
With regard to IATA/ICA	AO 2020:	
14.1	UN number:	UN1263
<b>** * * * 14.2</b>	UN proper shipping name:	PAINT
	Transport hazard class(es):	3
	Labels:	3
14.4	Packing group:	III
14.5	Environmental hazards:	Yes
14.6	Special precautions for user	
	Physico-Chemical properties:	see section 9
14.7	Transport in bulk according	Non-applicable
	to Annex II of Marpol and the IBC Code:	
	the IBC Coue.	

# SECTION 15: REGULATORY INFORMATION

15.1	Safety, health and environmental regulations/legislation specific for the substance or mixture:
	Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
	Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
	Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
	Article 95, REGULATION (EU) No 528/2012: Non-applicable
	REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable
	Seveso III:
1	- CONTINUED ON NEXT PAGE -



## SECTION 15: REGULATORY INFORMATION (continued)

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c		5000	50000
E2		200	500

# Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Contains more than 0.1 % of Toluene by weight. Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,

- artificial snow and frost,

- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,

decorative flakes and foams,

- artificial cobwebs.
- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

Product classified hazardous under the CMR. Sale and distribution to the general public is prohibited. Due to its CMR category, it is essential to apply the specific measures for workplace hazard prevention covered in articles 4 and 5 of the 2004/37/EC Directive and later modifications.

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

## Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

## Other legislation:

The product could be affected by sectorial legislation

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

## SECTION 16: OTHER INFORMATION \*\*

#### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

#### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- · Hazard statements
- · Precautionary statements
- · Supplementary information

## Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation

- H336: May cause drowsiness or dizziness
- H411: Toxic to aquatic life with long lasting effects
- H317: May cause an allergic skin reaction
- H360: May damage fertility or the unborn child
- H304: May be fatal if swallowed and enters airways
- H226: Flammable liquid and vapour

\*\* Changes with regards to the previous version



SECTION 16: OTHER INFORMATION ** (continued)
Texts of the legislative phrases mentioned in section 3:
The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the
individual components which appear in section 3
CLP Regulation (EC) No 1272/2008:
Acute Tox. 4: H312 - Harmful in contact with skin
Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled
Aquatic Acute 1: H400 - Very toxic to aquatic life
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways
Carc. 2: H351 - Suspected of causing cancer
Eye Dam. 1: H318 - Causes serious eye damage
Eye Irrit. 2: H319 - Causes serious eye irritation
Flam. Lig. 2: H225 - Highly flammable liquid and vapour
Flam. Liq. 3: H226 - Flammable liquid and vapour
Repr. 1B: H360 - May damage fertility or the unborn child
Repr. 2: H361d - Suspected of damaging the unborn child.
Skin Irrit. 2: H315 - Causes skin irritation
Skin Sens. 1: H317 - May cause an allergic skin reaction
Skin Sens. 1A: H317 - May cause an allergic skin reaction
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure
STOT SE 3: H336 - May cause drowsiness or dizziness
Classification procedure:
Skin Irrit. 2: Calculation method
STOT SE 3: Calculation method
Aquatic Chronic 2: Calculation method
Skin Sens. 1A: Calculation method
Repr. 1B: Calculation method
Asp. Tox. 1: Calculation method
Flam. Liq. 3: Calculation method (2.6.4.3)
Advice related to training:
Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.
Principal bibliographical sources:
http://echa.europa.eu
http://eur-lex.europa.eu
Abbreviations and acronyms:
ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol-water partition coefficient
Koc: Partition coefficient of organic carbon

\*\* Changes with regards to the previous version

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.