





**MORAVIA - MORACRYLIC HARDENER (COMPONENT B)  
SK48-1503B**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

- 1.1 Product identifier:** MORAVIA - MORACRYLIC HARDENER (COMPONENT B)  
SK48-1503B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses: Hardener for coatings. For professional user/industrial user only.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
MORAVIA BOYA VE KİMYA SAN.TİC.LTD.ŞTİ  
FEVZİ ÇAKMAK CADDESİ NO:2 SEFAKÖY/ KÜÇÜKÇEKMECE  
İSTANBUL - TURKEY  
Phone.: +90 212 579 13 36 - Fax: +90 212 426 55 12  
moravia@moravia.com.tr  
www.moravia.com.tr
- 1.4 Emergency telephone number:**

**SECTION 2: HAZARDS IDENTIFICATION \*\***

- 2.1 Classification of the substance or mixture:**  
**CLP Regulation (EC) No 1272/2008:**  
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.  
Acute Tox. 4: Acute inhalation toxicity, Category 4, H332  
Flam. Liq. 3: Flammable liquids, Category 3, H226  
Skin Irrit. 2: Skin irritation, Category 2, H315  
Skin Sens. 1: Sensitisation, skin, Category 1, H317  
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335
- 2.2 Label elements:**  
**CLP Regulation (EC) No 1272/2008:**  
**Warning**
-  
- Hazard statements:**  
Acute Tox. 4: H332 - Harmful if inhaled  
Flam. Liq. 3: H226 - Flammable liquid and vapour  
Skin Irrit. 2: H315 - Causes skin irritation  
Skin Sens. 1: H317 - May cause an allergic skin reaction  
STOT SE 3: H335 - May cause respiratory irritation
- Precautionary statements:**  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P280: Wear protective gloves/protective clothing/eye protection/face protection  
P302+P352: IF ON SKIN: Wash with plenty of water  
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P370+P378: In case of fire: Use ABC powder extinguisher to extinguish  
P403+P233: Store in a well-ventilated place. Keep container tightly closed  
P403+P235: Store in a well-ventilated place. Keep cool  
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively
- Supplementary information:**  
EUH204: Contains isocyanates. May produce an allergic reaction
- Substances that contribute to the classification**  
Hexamethylene diisocyanate, oligomers; Xylene; Hexamethylene-di-isocyanate
- 2.3 Other hazards:**  
Product fails to meet PBT/vPvB criteria

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**MORAVIA - MORACRYLIC HARDENER (COMPONENT B)  
SK48-1503B**

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1 Substance:**

Non-applicable

**3.2 Mixture:**

**Chemical description:** Miscellaneous products

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 28182-81-2 EC: 931-274-8 Index: Non-applicable REACH: 01-2119485796-17-XXXX	<b>Hexamethylene diisocyanate, oligomers<sup>(1)</sup></b> Self-classified Regulation 1272/2008 Acute Tox. 4: H332; Skin Sens. 1: H317; STOT SE 3: H335 - Warning	25 - <50 %
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX	<b>2-methoxy-1-methylethyl acetate<sup>(2)</sup></b> ATP ATP01 Regulation 1272/2008 Flam. Liq. 3: H226 - Warning	25 - <50 %
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	<b>Xylene<sup>(1)</sup></b> ATP CLP00 Regulation 1272/2008 Acute Tox. 4: H312+H332; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning	10 - <25 %
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	<b>N-butyl acetate<sup>(1)</sup></b> ATP CLP00 Regulation 1272/2008 Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	2,5 - <10 %
CAS: 822-06-0 EC: 212-485-8 Index: 615-011-00-1 REACH: 01-2119457571-37-XXXX	<b>Hexamethylene-di-isocyanate<sup>(1)</sup></b> ATP CLP00 Regulation 1272/2008 Acute Tox. 3: H331; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - Danger	<1 %

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

<sup>(2)</sup> Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**SECTION 4: FIRST AID MEASURES**

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

- CONTINUED ON NEXT PAGE -

**MORAVIA - MORACRYLIC HARDENER (COMPONENT B)  
SK48-1503B**

**SECTION 5: FIREFIGHTING MEASURES**

**5.1 Extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**6.2 Environmental precautions:**

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:**

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

- CONTINUED ON NEXT PAGE -



**MORAVIA - MORACRYLIC HARDENER (COMPONENT B)  
SK48-1503B**

**SECTION 7: HANDLING AND STORAGE (continued)**

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Technical measures for storage

Minimum Temp.: 5 °C  
Maximum Temp.: 30 °C  
Maximum time: 6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace

Identification	Occupational exposure limits		
	IOELV (8h)	IOELV (STEL)	IOELV (STEL)
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	50 ppm	100 ppm	275 mg/m <sup>3</sup> 550 mg/m <sup>3</sup>
Xylene CAS: 1330-20-7 EC: 215-535-7	50 ppm	100 ppm	221 mg/m <sup>3</sup> 442 mg/m <sup>3</sup>

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	1 mg/m <sup>3</sup>	Non-applicable	0,5 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	153,5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	275 mg/m <sup>3</sup>	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	180 mg/kg	Non-applicable
	Inhalation	289 mg/m <sup>3</sup>	289 mg/m <sup>3</sup>	77 mg/m <sup>3</sup>	Non-applicable
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	960 mg/m <sup>3</sup>	960 mg/m <sup>3</sup>	480 mg/m <sup>3</sup>	480 mg/m <sup>3</sup>
Hexamethylene-di-isocyanate CAS: 822-06-0 EC: 212-485-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	0,07 mg/m <sup>3</sup>	0,07 mg/m <sup>3</sup>	0,035 mg/m <sup>3</sup>	0,035 mg/m <sup>3</sup>

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	1,67 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	54,8 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	33 mg/m <sup>3</sup>	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	1,6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	108 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	14,8 mg/m <sup>3</sup>	Non-applicable
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	859,7 mg/m <sup>3</sup>	859,7 mg/m <sup>3</sup>	102,34 mg/m <sup>3</sup>	102,34 mg/m <sup>3</sup>

**PNEC:**

- CONTINUED ON NEXT PAGE -

**MORAVIA - MORACRYLIC HARDENER (COMPONENT B)**  
**SK48-1503B**
**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**



Identification				
Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8	STP	38,3 mg/L	Fresh water	0,127 mg/L
	Soil	53182 mg/kg	Marine water	0,0127 mg/L
	Intermittent	1,27 mg/L	Sediment (Fresh water)	266700 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	26670 mg/kg
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	STP	100 mg/L	Fresh water	0,635 mg/L
	Soil	0,29 mg/kg	Marine water	0,0635 mg/L
	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L
	Soil	2,31 mg/kg	Marine water	0,327 mg/L
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L
	Soil	0,0903 mg/kg	Marine water	0,018 mg/L
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,0981 mg/kg
Hexamethylene-di-isocyanate CAS: 822-06-0 EC: 212-485-8	STP	8,42 mg/L	Fresh water	0,0774 mg/L
	Soil	0,0026 mg/kg	Marine water	0,00774 mg/L
	Intermittent	0,774 mg/L	Sediment (Fresh water)	0,01334 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,001344 mg/kg

**8.2 Exposure controls:**
**A.- General security and hygiene measures in the work place**



As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

**C.- Specific protection for the hands**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2003+A1:2009 and EN ISO 374-1:2016

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"





**D.- Ocular and facial protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2001 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.



**E.- Body protection**

- CONTINUED ON NEXT PAGE -

**MORAVIA - MORACRYLIC HARDENER (COMPONENT B)**  
**SK48-1503B**
**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Antistatic and fireproof protective clothing		EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2001 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
 Mandatory foot protection	Safety footwear with antistatic and heat resistant properties		EN ISO 13287:2012 EN ISO 20345:2011	Replace boots at any sign of deterioration.

**F.- Additional emergency measures**

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	64,38 % weight
V.O.C. density at 20 °C:	635,04 kg/m <sup>3</sup> (635,04 g/L)
Average carbon number:	6,73
Average molecular weight:	121,26 g/mol

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**
**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Not available
Colour:	Not available
Odour:	Not available
Odour threshold:	Non-applicable *

**Volatility:**

Boiling point at atmospheric pressure:	141 °C
Vapour pressure at 20 °C:	608 Pa
Vapour pressure at 50 °C:	3413,69 Pa (3,41 kPa)
Evaporation rate at 20 °C:	Non-applicable *

**Product description:**

Density at 20 °C:	956,5 - 1016,5 kg/m <sup>3</sup>
Relative density at 20 °C:	0,956 - 1,016
Dynamic viscosity at 20 °C:	3000 cP
Kinematic viscosity at 20 °C:	3041,15 cSt
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**MORAVIA - MORACRYLIC HARDENER (COMPONENT B)  
SK48-1503B**

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
<b>Flammability:</b>	
Flash Point:	35 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	315 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available
<b>Explosive:</b>	
Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *
<b>9.2 Other information:</b>	
Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:**

Chemically stable under the conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

- CONTINUED ON NEXT PAGE -

**MORAVIA - MORACRYLIC HARDENER (COMPONENT B)  
SK48-1503B**

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.  
IARC: Xylene (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Skin: Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23,4 mg/L (4 h)	Rat
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg (ATEi)	Rat
	LC50 inhalation	11 mg/L (4 h) (ATEi)	

- CONTINUED ON NEXT PAGE -





**MORAVIA - MORACRYLIC HARDENER (COMPONENT B)**  
**SK48-1503B**

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	8532 mg/kg	5100 mg/kg	Rat
Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8	30 mg/L (4 h)		Rat
	LD50 oral	5100 mg/kg	Rat
	LD50 dermal	Non-applicable	
Hexamethylene-di-isocyanate CAS: 822-06-0 EC: 212-485-8	11 mg/L (4 h) (ATEi)		
	LD50 oral	Non-applicable	
	LD50 dermal	Non-applicable	
	3 mg/L (4 h) (ATEi)		Rat

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

**12.1 Toxicity:**

Identification	Acute toxicity		Species	Genus
	LC50	EC50		
Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8	Non-applicable			
	Non-applicable			
	1000 mg/L (72 h)		Scenedesmus subspicatus	Algae
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	161 mg/L (96 h)		Pimephales promelas	Fish
	481 mg/L (48 h)		Daphnia sp.	Crustacean
	Non-applicable			
Xylene CAS: 1330-20-7 EC: 215-535-7	13.5 mg/L (96 h)		Oncorhynchus mykiss	Fish
	3.4 mg/L (48 h)		Ceriodaphnia dubia	Crustacean
	10 mg/L (72 h)		Skeletonema costatum	Algae
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	62 mg/L (96 h)		Leuciscus idus	Fish
	73 mg/L (24 h)		Daphnia magna	Crustacean
	675 mg/L (72 h)		Scenedesmus subspicatus	Algae

**12.2 Persistence and degradability:**

Identification	Degradability		Biodegradability	
	BOD5	COD	Concentration	Period
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Non-applicable	Non-applicable	785 mg/L	8 days
	Non-applicable	Non-applicable	% Biodegradable	100 %
	Non-applicable	Non-applicable		
Xylene CAS: 1330-20-7 EC: 215-535-7	Non-applicable	Non-applicable	Non-applicable	28 days
	Non-applicable	Non-applicable	% Biodegradable	88 %
	Non-applicable	Non-applicable		
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Non-applicable	Non-applicable	Non-applicable	5 days
	Non-applicable	Non-applicable	% Biodegradable	84 %
	0.79			
Hexamethylene-di-isocyanate CAS: 822-06-0 EC: 212-485-8	Non-applicable	Non-applicable	100 mg/L	28 days
	Non-applicable	Non-applicable		
	Non-applicable	Non-applicable	% Biodegradable	28 %

**12.3 Bioaccumulative potential:**

Identification	Bioaccumulation potential	
	BCF	Pow Log
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	1	0.43
		Low
Xylene CAS: 1330-20-7 EC: 215-535-7	9	2.77
		Low
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	4	1.78
		Low

- CONTINUED ON NEXT PAGE -

**MORAVIA - MORACRYLIC HARDENER (COMPONENT B)**  
**SK48-1503B**
**SECTION 12: ECOLOGICAL INFORMATION (continued)**
**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable

**12.5 Results of PBT and vPvB assessment:**

Product fails to meet PBT/vPvB criteria

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**
**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

**Type of waste (Regulation (EU) No 1357/2014):**

HP3 Flammable, HP3 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**
**Transport of dangerous goods by land:**

With regard to ADR 2019 and RID 2019:



- 14.1 UN number:** UN1263  
**14.2 UN proper shipping name:** PAINT RELATED MATERIAL  
**14.3 Transport hazard class(es):** 3  
 Labels: 3  
**14.4 Packing group:** III  
**14.5 Environmental hazards:** No  
**14.6 Special precautions for user**  
 Special regulations: 163, 367, 650  
 Tunnel restriction code: D/E  
 Physico-Chemical properties: see section 9  
 Limited quantities: 5 L  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 39-18:

- CONTINUED ON NEXT PAGE -

**MORAVIA - MORACRYLIC HARDENER (COMPONENT B)  
SK48-1503B**

**SECTION 14: TRANSPORT INFORMATION (continued)**



- 14.1 UN number:** UN1263  
**14.2 UN proper shipping name:** PAINT RELATED MATERIAL  
**14.3 Transport hazard class(es):** 3  
 Labels: 3  
**14.4 Packing group:** III  
**14.5 Environmental hazards:** No  
**14.6 Special precautions for user**  
 Special regulations: 163, 223, 955, 367  
 EmS Codes: F-E, S-E  
 Physico-Chemical properties: see section 9  
 Limited quantities: 5 L  
 Segregation group: Non-applicable  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2020:



- 14.1 UN number:** UN1263  
**14.2 UN proper shipping name:** PAINT RELATED MATERIAL  
**14.3 Transport hazard class(es):** 3  
 Labels: 3  
**14.4 Packing group:** III  
**14.5 Environmental hazards:** No  
**14.6 Special precautions for user**  
 Physico-Chemical properties: see section 9  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable  
 Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable  
 Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable  
 Article 95, REGULATION (EU) No 528/2012: Non-applicable  
 REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Seveso III:**

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c		5000	50000

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

- CONTINUED ON NEXT PAGE -



**MORAVIA - MORACRYLIC HARDENER (COMPONENT B)  
SK48-1503B**

**SECTION 15: REGULATORY INFORMATION (continued)**

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

The product could be affected by sectorial legislation

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION**

**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Supplementary information

**Texts of the legislative phrases mentioned in section 2:**

H317: May cause an allergic skin reaction

H335: May cause respiratory irritation

H315: Causes skin irritation

H332: Harmful if inhaled

H226: Flammable liquid and vapour

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) No 1272/2008:**

Acute Tox. 3: H331 - Toxic if inhaled

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled

Acute Tox. 4: H332 - Harmful if inhaled

Eye Irrit. 2: H319 - Causes serious eye irritation

Flam. Liq. 3: H226 - Flammable liquid and vapour

Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction

STOT SE 3: H335 - May cause respiratory irritation

STOT SE 3: H336 - May cause drowsiness or dizziness

**Classification procedure:**

- CONTINUED ON NEXT PAGE -



**MORAVIA - MORACRYLIC HARDENER (COMPONENT B)  
SK48-1503B**

**SECTION 16: OTHER INFORMATION (continued)**

Skin Sens. 1: Calculation method  
STOT SE 3: Calculation method  
Skin Irrit. 2: Calculation method  
Acute Tox. 4: Calculation method  
Flam. Liq. 3: Calculation method (2.6.4.3)

**Advice related to training:**

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5-day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
LC50: Lethal Concentration 50  
EC50: Effective concentration 50  
Log-POW: Octanol-water partition coefficient  
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -